

SK 600x600

SK 600x600 LED 5000K Ra>90 450/500mA

PL

Rodzaj montażu: **wpuszczany**

Źródło światła: **LED**

Temperatura barwowa: **5000K**

Strumień świetlny: **6360/7020lm**

CRI: **90**

Moc: **48/54W**

Napięcie: **230V**

Żywotność: **50.000h**

Waga: **5,1kg**

Kolor obudowy: **RAL**

Sterowanie: **opcja**

Otwór montażowy: **580x580mm**

ENG

Method of installation: **recessed**

Light sources: **LED**

Color temperature: **5000K**

Initial luminous flux: **6360/7020lm**

CRI: **90**

Initial input power: **48/54W**

Input Voltage: **230V**

Lumen maintenance: **50.000h**

Weight: **5,1kg**

Housing colour: **RAL**



Dimmable: **optional**

Mounting hole: **580x580mm**

Tolerancja strumienia świetlnego i mocy +/- 10%
Producent zastrzega sobie możliwość zmian konstrukcyjnych oprawy.
Istnieje możliwość modyfikacji produktu na życzenie Klienta.
Informacje zawarte na karcie katalogowej nie stanowią oferty handlowej ani elementu umowy.
Więcej na temat rodziny produktów, znajduje się na stronie: www.lako.pl

Luminous flux and power tolerance +/- 10%
The manufacturer reserves the right to change the design of the luminaire.
It is possible to modify the product at the customer's request.
The information contained in the catalog card does not constitute a commercial offer or an element of the contract.
More information about the product family can be found at: www.lako.pl

LAKO



Klinika stomatologiczna, SMILE SERVICE, Świnoujście
SMILE SERVICE dental clinic, Świnoujście



Obudowa w dowolnym kolorze RAL
Housing in any RAL colour