



TILE N 80x1500 PEND

TILE N 80 x 1500 PEND LED HO 3000/4000K 375mA

PL

Rodzaj montażu: **zwieszany**

Źródło światła: **LED**

Temperatura barwowa: **3000/4000K**

Strumień świetlny: **7275/7650lm**

Moc: **42W**

Napięcie: **230V**

Żywotność: **72.000h**

Waga: **4kg**

Kolor obudowy: **RAL**

Sterowanie: **opcja**

ENG

Method of installation: **suspended**

Light sources: **LED**

Color temperature: **3000/4000K**

Initial luminous flux: **7275/7650lm**

Initial input power: **42W**

Input Voltage: **230V**

Service life: **72.000h**

Weight: **4kg**



Housing colour: **RAL**

Dimmable: **optional**

Tolerancja strumienia świetlnego i mocy +/- 10%
Producent zastrzega sobie możliwość zmian konstrukcyjnych oprawy.
Istnieje możliwość modyfikacji produktu na życzenie Klienta.
Informacje zawarte na karcie katalogowej nie stanowią oferty handlowej ani elementu umowy.
Więcej na temat rodziny produktów, znajduje się na stronie: www.lako.pl

Luminous flux and power tolerance +/- 10%
The manufacturer reserves the right to change the design of the luminaire.
It is possible to modify the product at the request of customers.
The pieces of information contained in the catalogue card constitute neither a commercial offer nor an element of the contract.
More information about the product family may be found on the website: www.lako.pl

LAKO



Biuro ALL IN GAMES, Kraków
ALL IN GAMES office, Cracow



Biuro TRECOM, Kraków
TRECOM office, Cracow



Obudowa w dowolnym kolorze RAL
Housing in any RAL colour