




LAKO



SSFN THIN LED PEND

SSFN THIN LED PEND 605x605 3000/4000K 375mA

PL

Rodzaj montażu: **zwieszana**

Źródło światła: **LED**

Temperatura barwowa: **3000/4000K**

Strumień świetlny: **8077/8365lm**

CRI: **80**

Moc: **44W**

Napięcie: **230V**

Żywotność: **72.000h**

Waga: **7kg**

Kolor obudowy: **RAL**

Sterowanie: **opcja**

ENG

Method of installation: **suspended**

Light sources: **LED**

Color temperature: **3000/4000K**

Initial luminous flux: **8077/8365lm**

CRI: **80**

Initial input power: **44W**

Input Voltage: **230V**

Lumen maintenance: **72.000h**

Weight: **7kg**

Housing colour: **RAL**

Dimmable: **optional**



Salon ART CINEMA, Warszawa
ART CINEMA store, Warsaw



Biurowiec LABEO, Kraków
LABEO office, Cracow

Tolerancja strumienia świetlnego i mocy +/- 10%
Producent zastrzega sobie możliwość zmian konstrukcyjnych oprawy.
Istnieje możliwość modyfikacji produktu na życzenie Klienta.
Informacje zawarte na karcie katalogowej nie stanowią oferty handlowej ani elementu umowy.
Więcej na temat rodziny produktów, znajduje się na stronie: www.lako.pl

Luminous flux and power tolerance +/- 10%
The manufacturer reserves the right to change the design of the luminaire.
It is possible to modify the product at the customer's request.
The information contained in the catalog card does not constitute a commercial offer or an element of the contract.
More information about the product family can be found at: www.lako.pl



Obudowa w dowolnym kolorze RAL
Housing in any RAL colour