

LSS LED

LSS 1137 4000K 450mA DALI

PL

Rodzaj montażu: **zwieszana**

Źródło światła: **LED**

Temperatura barwowa: **4000K**

Strumień świetlny: **3886lm**

Moc: **24W**

Napięcie: **230V**

Żywotność: **72.000h**

Waga: **1,6kg**

Kolor obudowy: **biały**

Sterowanie: **tak (DALI)**

ENG

Method of installation: **suspended**

Light sources: **LED**

Color temperature: **4000K**

Initial luminous flux: **3886m**

Initial input power: **24W**

Input Voltage: **230V**


Service life: **72.000h**

Weight: **1,6kg**

Housing colour: **white**

Control: **yes (DALI)**

LAKO



Wymiary
Dimensions

a - 1137mm,
b - 92mm,
d - 51mm,



Sklep ŻABKA, Warszawa
ŻABKA shop, Warsaw



Sklep LEWIATAN, Wolbrom
LEWIATAN shop, Wolbrom

Tolerancja strumienia świetlnego i mocy +/- 10%
Producent zastrzega sobie możliwość zmian konstrukcyjnych oprawy.
Istnieje możliwość modyfikacji produktu na życzenie Klienta.
Informacje zawarte na karcie katalogowej nie stanowią oferty handlowej ani elementu umowy.
Więcej na temat rodziny produktów, znajduje się na stronie: www.lako.pl

Luminous flux and power tolerance +/- 10%
The manufacturer reserves the right to change the design of the luminaire.
It is possible to modify the product at the request of customers.
The pieces of information contained in the catalogue card constitute neither a commercial offer nor an element of the contract.
More information about the product family may be found on the website: www.lako.pl



Obudowa w dowolnym RAL
Housing in any RAL colour