

# ADBOX MINI

ADBOX MINI 1xLED  
ADBOX MINI 2xLED  
ADBOX MINI 3xLED

## PL

Rodzaj montażu: <b>nastropowy</b>	Method of installation: <b>mounted on the ceiling</b>
Źródło światła: <b>LED</b>	Light sources: <b>LED</b>
Temperatura barwowa: <b>3000/4000K</b>	Color temperature: <b>3000/4000K</b>
Strumień świetlny: <b>350/575lm*</b>	Initial luminous flux: <b>350/575lm*</b>
Moc: <b>4,3/6,9W*</b>	Initial input power: <b>4,3/6,9W*</b>
Napięcie: <b>230V</b>	Input Voltage: <b>230V</b>
Żywotność: <b>15.000h</b>	Service life: <b>15.000h</b>
Waga: <b>1,2kg*</b>	Weight: <b>1,2kg*</b>
Kolor obudowy: <b>RAL</b>	Housing colour: <b>RAL</b>


\*pojedynczy element

\*single element

Tolerancja strumienia świetlnego i mocy +/- 10%  
Producent zastrzega sobie możliwość zmian konstrukcyjnych oprawy.  
Istnieje możliwość modyfikacji produktu na życzenie Klienta.  
Informacje zawarte na karcie katalogowej nie stanowią oferty handlowej ani elementu umowy.  
Więcej na temat rodziny produktów, znajduje się na stronie: [www.lako.pl](http://www.lako.pl)

Luminous flux and power tolerance +/- 10%  
The manufacturer reserves the right to change the design of the luminaire.  
It is possible to modify the product at the request of customers.  
The pieces of information contained in the catalogue card constitute neither a commercial offer nor an element of the contract.  
More information about the product family may be found on the website: [www.lako.pl](http://www.lako.pl)

# LAKO



Koncept LAKO  
LAKO concept



Dom prywatny, Wolbrom  
Private house, Wolbrom

Obudowa w dowolnym RAL  
Housing in any RAL colour

